

## Horizontal Lifting Clamp TDH

### Product information



Lightweight heavy duty clamp for safe and easy lifting of sheets that will bend or deflect when being lifted. The TDH horizontal lifting clamps must always be used in pairs (or multiples thereof).

#### Features:

- Compact design and high lifting capacity
- Lightweight design for easy handling
- Tough quality heavy duty welded body

**Marking:** According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

**Temperature range:** - 40°C to +100°C.

**Standard:** EN 13155

**Note:** Must always be used in pairs (or multiple pairs)

**Warning:** Hardness level of the material surface may not exceed 37 Hrc (345 Hb, 1166 N/mm<sup>2</sup>)

| Part Code       | Code  | WLL ton | Jaw width mm | H mm | S mm | T mm | U mm | V mm | W mm | X mm | Y mm | Weight kg |
|-----------------|-------|---------|--------------|------|------|------|------|------|------|------|------|-----------|
| 502100100150690 | 1 TDH | 1       | 0-15         | 13.5 | 99   | 22.5 | 167  | 140  | 10   | 65   | 15   | 2.5       |
| 502100200350690 | 2 TDH | 2       | 0-35         | 14   | 114  | 26   | 233  | 180  | 20   | 80   | 15   | 8         |
| 502100400500690 | 4 TDH | 4       | 0-50         | 25   | 129  | 40   | 304  | 235  | 30   | 130  | 20   | 18        |
| 502100600500690 | 6 TDH | 6       | 0-50         | 25   | 129  | 40   | 304  | 235  | 30   | 130  | 20   | 18        |

## Blueprint

