



Mobile crane



Crawler crane



Verotop S+

Product information



Wire rope construction: Verotop S+ is a very flexible rotation-resistant rope with compacted outer strands and extraordinary high breaking strength.

Features:

- The strongest of all compacted rotation-resistant ropes.
- Achieves very good bending fatigue results.
- Offers excellent resistance to crushing and abrasion.
- Possesses perfect spooling behavior on multilayer drum.
- Can be used either with or without swivel.

ISO 4309 Rope Category No: All Diameters RCN.23-2

Marking: According to standard

Standard: EN 12385-4

Fill factor: 0.742

Tolerance Ø: +2% to +4%

Part Code	Rope Diameter, mm	Steel area mm ²	Min. Breaking force kN. 1960 N/mm ²	Weight kg/100m
104101305070179	13	98.4	179	86.7
104101405070179	14	114	208	101
104101505070179	15	131	239	115
104101605070179	16	149	271	131

104101705070179	17	168	306	148
104101805070179	18	189	343	166
104101905070179	19	210	383	185
104102005070179	20	233	424	205
104102105070179	21	257	467	226
104102205070179	22	289	513	248
104102305070179	23	308	561	271
104102405070179	24	336	611	295
104102505070179	25	364	663	321
104102605070179	26	394	717	347
104102705070179	27	425	773	374
104102805070179	28	457	831	402
104102905070179	29	490	891	431
104103005070179	30	524	954	462
104103105070179	31	560	1019	493
104103205070179	32	596	1085	525
104103305070179	33	634	1154	559
104103405070179	34	673	1225	593
104103505070179	35	714	1298	628
104103605070179	36	755	1374	665
104103805070179	38	841	1531	741
104104005070179	40	932	1696	821