

Pipe and Test Sealing Bag

Product information



The sealing bags are suitable for all kind of pipe dimensions, models and materials. The operating pressure is between 0,5 til 6 bars depending on size and pressure in the pipe. Can be used to prevent or reroute sewagewater from reaching the groundwater or for bypass when repairing or pressure testing a pipe. Can also be used as a help when welding two pipes together by using the Vetter bag as a fix for the pipe ends.

All pipe sealing bags are available as test sealing bags with one or two bypasses. For more information please contact your CERTEX office.

Material: Vulcanized reinforced rubber.

Temperature range: -20°C up to +90°C.

Note: For more information please contact your CERTEX office.

Part code	Workingpressure bar	Pipe Ø mm	Cylinder Ø mm	Cylinderlength mm	Total length mm	Weight kg
56111440000101	2,5	25-40	21	115	175	0.15
56111440000201	2,5	40-70	37	155	215	0.2
56111440000301	2,5	70-150	68	300	345	0.5
56111440011700	2,5	100-200	90	510	555	1.2
56111440000601	2,5	150-300	145	350	395	1.41
56111440016700	2,5	200-500	195	750	795	5
56111440000801	2,5	300-600	295	735	780	7
56111440028200	1,5	500-1000	450	1,110	1,155	17
56111480001901	1,5	600-1200	580	1,320	1,365	25
56111480006000	1,5	800-1400	785	1,810	1,855	41
56111400000300	0,5	1400-1700	1,350	1,900	2,150	55
56111400000100	0,5	1700-2000	1,620	1,900	2,300	59