

## Pipe and Test Sealing Bag

### Product information



The sealing bags are suitable for all kind of pipe dimensions, models and materials. The operating pressure is between 0,5 til 6 bars depending on size and pressure in the pipe. Can be used to prevent or reroute sewagewater from reaching the groundwater or for bypass when repairing or pressure testing a pipe. Can also be used as a help when welding two pipes together by using the Vetter bag as a fix for the pipe ends.

All pipe sealing bags are available as test sealing bags with one or two bypasses. For more information please contact your CERTEX office.

**Material:** Vulcanized reinforced rubber.

**Temperature range:** -20°C up to +90°C.

**Note:** For more information please contact your CERTEX office.

| Part Code      | Workingpressure<br>bar | Pipe Ø<br>mm | Cylinder Ø<br>mm | Cylinderlength<br>mm | Total length<br>mm | Weight<br>kg |
|----------------|------------------------|--------------|------------------|----------------------|--------------------|--------------|
| 56111440000101 | 2,5                    | 25-40        | 21               | 115                  | 175                | 0.15         |
| 56111440000201 | 2,5                    | 40-70        | 37               | 155                  | 215                | 0.2          |
| 56111440000301 | 2,5                    | 70-150       | 68               | 300                  | 345                | 0.5          |
| 56111440011700 | 2,5                    | 100-200      | 90               | 510                  | 555                | 1.2          |
| 56111440000601 | 2,5                    | 150-300      | 145              | 350                  | 395                | 1.41         |
| 56111440016700 | 2,5                    | 200-500      | 195              | 750                  | 795                | 5            |
| 56111440000801 | 2,5                    | 300-600      | 295              | 735                  | 780                | 7            |
| 56111440028200 | 1,5                    | 500-1000     | 450              | 1,110                | 1,155              | 17           |
| 56111480001901 | 1,5                    | 600-1200     | 580              | 1,320                | 1,365              | 25           |
| 56111480006000 | 1,5                    | 800-1400     | 785              | 1,810                | 1,855              | 41           |
| 56111400000300 | 0,5                    | 1400-1700    | 1,350            | 1,900                | 2,150              | 55           |
| 56111400000100 | 0,5                    | 1700-2000    | 1,620            | 1,900                | 2,300              | 59           |