



Master Link Grab 1 Assy X-A04, Yoke

Product information

Fully integrated shortening hook and master link.
At least 25% greater WLL than traditional Grade 8 products.
Fatigue rated to 20,000 cycles at 1.5 times the WLL.
No reduction in WLL when shortening chain.
Speedy assembly.
Light weight system.
Cost effective compared to slings which use multiple components.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

| Part Code | Chain diameter mm | WLL ton | DIN 15401 Hook No. | D mm | A mm | B mm | K mm | Weight kg |
|--------------|----------------------|------------|--------------------|---------|---------|---------|---------|--------------|
| 402100140460 | 6 | 1.4 | 4 | 13 | 120 | 70 | 196 | 0.7 |
| 402100250460 | 8 | 2.5 | 5 | 16 | 140 | 80 | 242 | 1.2 |
| 402100400460 | 10 | 4 | 6 | 19 | 160 | 95 | 285 | 2.1 |
| 402100670460 | 13 | 6.7 | 10 | 22 | 170 | 105 | 328 | 3.9 |
| 402101000460 | 16 | 10 | 10 | 28 | 190 | 110 | 392 | 7 |
| 402101600460 | 20 | 16 | 12 | 32 | 230 | 130 | 483 | 10 |
| 402101900460 | 22 | 19 | 20 | 38 | 275 | 150 | 591 | 14.4 |

Blueprint

