



## Connecting Link X-015 Grade 10

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 8 and Grade 10 chain.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

| Part Code    | Chain diameter<br>mm | WLL<br>ton | A<br>mm | B<br>mm | D<br>mm | K<br>mm | Weight<br>kg |
|--------------|----------------------|------------|---------|---------|---------|---------|--------------|
| 402200140190 | 6                    | 1.4        | 15      | 17      | 7       | 45      | 0.08         |
| 402200250190 | 7-8                  | 2.5        | 18      | 23      | 9       | 59      | 0.2          |
| 402200400190 | 10                   | 4          | 25      | 27      | 11      | 69      | 0.3          |
| 402200670190 | 13                   | 6.7        | 30      | 37      | 16      | 92      | 0.7          |
| 402201000190 | 16                   | 10         | 36      | 39      | 19      | 101     | 1.2          |
| 402201600190 | 20                   | 16         | 42      | 46      | 23      | 122     | 2.1          |
| 402201900190 | 22                   | 19         | 49      | 59      | 24      | 152     | 3.5          |
| 402202650190 | 26                   | 26.5       | 55      | 62      | 30      | 162     | 4.8          |
| 402204000190 | 32                   | 40         | 69      | 79      | 36      | 203     | 9            |

## Blueprint

