



## Welded Master Link X-002W

### Product information

- Welded Master Link designed for 1-2 legs Wire Rope and Chain Slings.
- At least 25% greater WLL than traditional Grade 8 products.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and Tempered Alloy Steel

**Marking:** According to standard, CE-marked, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	For chain gr 10 Ø 2 leg mm	For chain gr 10 Ø 1 leg mm	Din 15401.NO	D mm	A mm	B mm	Weight kg
402100280500	CD-13	2.8	6	7,8	4	13	120	70	0.4
402100400500	CD-16	4	7,8	10	5	16	140	80	0.7
402100670500	CD-19	6.7	10	13	6	19	160	95	1.1
402100850500	CD-22	8.5	10	13	10	22	170	105	1.6
402101150500	CD-28	11.5	13	16	10	28	190	110	2.9
402101700500	CD-32	17	16	20	12	32	230	130	4.5
402102510500	CD-36	25.1	20	22	20	36	275	150	6.7

## Blueprint

