



Round Sling self locking Hook X-028

Product information

At least 25% greater WLL than traditional Grade 8 products.
 Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
 Fatigue rated to 20,000 cycles at 1.5 times the WLL.
 Tempering temperature minimum 400°C.
 Magnaflux crack detection is performed 100% on each batch.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	For Grade 100 Chain mm	H mm	K mm	P mm	T mm	W mm	Weight kg
402300140780	6	1.4	6	19	138	29	15	38	0.6
402300250780	7-8	2.5	7, 8	24	169	34	20	40	1
402300400780	10	4	10	30	196	44	26	47	1.8
402300670780	13	6.7	13	39	253	52	30	53	3.9
402301000780	16	10	16	49	305	60	36	67	6.9
402301600780	20	16	20	62	328	90	48	80	12
402301900780	22	19	22	63	416	80	49	125	18.6

Blueprint

