



Crane rope VS 16-2 C

Product information



Typical applications: Hoist rope for telescopic crane, harbour crane, offshore crane, mobile crane, rotating tower crane and lattice boom crane, where rotation-resistant rope is required.

Rope construction: Rotation-resistant, outer strands compacted, which provide better running properties.

Finish: Zinc-coated class B standard

Tower crane



Offshore crane



Mobile crane



Harbour mobile crane



Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
104100806270219	8	1,960	Galvanized	zZ	54.9	35.2	SupplierStandard	31.3
104100906270219	9	1,960	Galvanized	zZ	69.4	44.5	SupplierStandard	39.6
104101006270219	10	1,960	Galvanized	zZ	85.7	55	SupplierStandard	48.9
104101106270219	11	1,960	Galvanized	zZ	104	66.5	SupplierStandard	59.2
104101206270219	12	1,960	Galvanized	zZ	123	79.1	SupplierStandard	70.4
104101306270219	13	1,960	Galvanized	zZ	145	92.9	SupplierStandard	82.6
104101406270219	14	1,960	Galvanized	zZ	168	108	SupplierStandard	95.8
104101506270219	15	1,960	Galvanized	zZ	193	124	SupplierStandard	110
104101606270219	16	1,960	Galvanized	zZ	219	141	SupplierStandard	125
104101806270219	18	1,960	Galvanized	zZ	278	178	SupplierStandard	158
104102006270219	20	1,960	Galvanized	zZ	343	220	SupplierStandard	196
104102206270219	22	1,960	Galvanized	zZ	415	266	SupplierStandard	237
104102406270219	24	1,960	Galvanized	zZ	494	317	SupplierStandard	282
104102606270219	26	1,960	Galvanized	zZ	580	371	SupplierStandard	331
104102806270219	28	1,960	Galvanized	zZ	672	431	SupplierStandard	383
104103006270219	30	1,960	Galvanized	zZ	772	495	SupplierStandard	440