

Elevator rope 8x19S-IWRC

Product information



General: Steel wire rope for use in elevator.

Tolerance \varnothing : ≤ 10 mm 0% - +6%, > 10 mm 0% - +5%.

Rope construction: 8x19-IWRC.


Marking: According to standard

Finish: Ungalvanised

Standard: EN 12385-5

Fill factor: 0.59

Elevator



| Part Code | Rope Diameter, mm | Tensile strength N/mm ² | Finish | Rope lay. | Min. Breaking force, kN | Steel area mm ² | Lubrication | Weight kg/100m |
|-----------------|-------------------|------------------------------------|--------|-----------|-------------------------|----------------------------|------------------|----------------|
| 106100804020219 | 8 | 1,570 | Bright | sZ | 37.9 | 31.1 | SupplierStandard | 27 |
| 106100904020219 | 9 | 1,570 | Bright | sZ | 48 | 38.1 | SupplierStandard | 34 |
| 106101004020219 | 10 | 1,570 | Bright | sZ | 58.5 | 46.6 | SupplierStandard | 41 |
| 106101104020219 | 11 | 1,570 | Bright | sZ | 69.7 | 55.6 | SupplierStandard | 49 |
| 106101204020219 | 12 | 1,570 | Bright | sZ | 83.6 | 66.4 | SupplierStandard | 59 |
| 106101304020219 | 13 | 1,570 | Bright | sZ | 100 | 79.5 | SupplierStandard | 70 |
| 106101404020219 | 14 | 1,570 | Bright | sZ | 116 | 91.8 | SupplierStandard | 81 |
| 106101504020219 | 15 | 1,570 | Bright | sZ | 131 | 104 | SupplierStandard | 92 |
| 106101604020219 | 16 | 1,570 | Bright | sZ | 148 | 118 | SupplierStandard | 105 |