



Extension Ladder Euro Fall Control FEU-FC

Product information

General:

The Euro Fall Control Extension ladders are stronger than any other fibreglass ladders in the market, featuring a unique integrated fall protection system according to EN 353-2.

The guiding principles of the Branch Fall Control System:

- The worker is safe from the moment they leave the ground.
- The stability system works from the ground up.
- Fall control system stems from the increased base of support.
- The ladder is secured with an integrated tether system.
- Integrated rescue by second user from the ground.
- Allows workers to work from the ladder with both hands comfortably and safely.
- To meet and exceed compliance and international standards.
- Design fit for purpose, critical piece of climbing equipment.
- Periodic inspection schedule recommended.

Features:

- Cross Bar and Upper Pulley
- Run Work Position Hook
- Non-slip Rungs
- Tether Tensioner
- Box Rail Rung Joining System
- Tether Rope
- Rope Bag
- Vertical Lifeline (configured for rescue)
- Lower Tether Hooks
- Level Bubble
- Descender
- Extra Wide TerrainMaster

Material: Stiles: Fibreglass ISO-PE resin with e-glass fibre. Rungs: Aluminium 6060

Marking: According to standard

Standard: EN 131-2-2010 + A2:2017

Note: Max. load rate Ladder 150 kg. Fall Control 120 kg.

Part Code	Closed length min length m	ladder length, extended m	Weight kg
9098FEU39FC	2.9	3.89	23
9098FEU51FC	3.5	5.09	26
9098FEU63FC	4.1	6.29	29
9098FEU75FC	4.7	7.49	35.7
9098FEU87FC	5.3	8.69	39