

## Flexible Lanyards POWERTEX FL-2

### Product information



The Powertex FL-2 double-leg flexible lanyards are equipped with a shock absorber and approved for 140 kg use. These lanyards have an elastic quality that allows them to stretch in accordance with the user's movements. Both lanyards are securely sewn to a shock absorber pack, which includes a screw gate steel carabiner for attachment to a harness. On the other end of the lanyards, sewn-in double-action aluminum scaffold hooks provide reliable anchorage.

In the unlikely event of a fall, the shock absorber pack will rupture to absorb the energy of the fall. If this happens, it reveals a white webbing that serves as a fall indicator. This feature lets users quickly identify if a lanyard has been used in a fall and must be removed from service.

The FL-2 double-leg flexible lanyards are manufactured to the highest standards and are designed to provide reliable fall protection for those who work at heights. It's also RFID-equipped (HF 13,56 MHz chip) for easy service, inspection, and asset control.

**Carabiner:** Screw gate carabiner (23 kN) acc to EN 362 marked with serial number

**Scaffold hooks:** Double action scaffold hook with an eye (23 kN) acc to EN 362 with 60 mm opening.

**Hand washing:** Allowed up to +40°C with mild detergent.

**Features:** CE & UKCA approved

**Material:** Polyester lanyard, Polyester shock absorber, Steel carabiner, Aluminum scaffold hooks

**Marking:** According to standard, CE-marked, UKCA-marked, Supplier symbol, Product identification, Max weight, Length (Nom), Length (Max), Production date, Serial number.

**Temperature range:** -35°C up to +50°C

**Standard:** EN 355

Part Code	Length m	Max load kg	Weight kg
821100142320	1.4	140	1.6