



## Master link oversized, grade 80

### Product information

Extra large masterlink for chain sling assemblies.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

| Part Code    | WLL ton | For chain mm, 1-leg | For chain mm, 2-leg | A mm | B mm | D mm | Weight kg |
|--------------|---------|---------------------|---------------------|------|------|------|-----------|
| 401100320270 | 3.2     | 10                  | 7/8                 | 190  | 100  | 16   | 0.86      |
| 401100700270 | 7       | 13                  | 10                  | 210  | 110  | 22   | 1.83      |
| 401101150270 | 11.5    | 16                  | 13/16               | 270  | 140  | 28   | 3.8       |
| 401101700270 | 17      | 22                  | 20                  | 270  | 140  | 32   | 5.05      |
| 401101900270 | 19      | 22                  | 20                  | 420  | 220  | 38   | 10.78     |
| 401102800270 | 25.1    | 26                  | 22                  | 270  | 140  | 38   | 7.29      |
| 401102700270 | 27      | 26                  | 22                  | 470  | 250  | 45   | 17.06     |
| 401104500270 | 45      | 36                  | 32                  | 380  | 200  | 50   | 17.65     |
| 401106500270 | 65      | 36                  | 32                  | 430  | 220  | 60   | 28.85     |

## Blueprint

