



## Eye self-locking hook with ball bearing swivel, grade 80

### Product information

The hook locks automatically when lifting starts and rotates easily also with full load.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-3

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

| Part Code    | WLL ton | For chain dia. mm | A mm | B mm | C mm | L1 mm | L mm | T mm | E mm | M mm | N mm | Ø mm | Weight kg |
|--------------|---------|-------------------|------|------|------|-------|------|------|------|------|------|------|-----------|
| 420500200890 | 2       | 7/8               | 36   | 13   | 40   | 202   | 240  | 35   | 39   | 88   | 20   | 44   | 1.1       |
| 420500320890 | 3.15    | 10                | 42   | 16   | 48   | 237   | 283  | 45   | 48   | 108  | 26   | 58   | 2         |
| 420500530890 | 5.3     | 13                | 50   | 17   | 58   | 282   | 343  | 52   | 65   | 134  | 33   | 70   | 4         |
| 420500800890 | 8       | 16                | 61   | 22   | 60   | 342   | 419  | 63   | 65   | 169  | 38   | 86   | 7.3       |
| 420501250890 | 12.5    | 20                | 76   | 27   | 75   | 400   | 483  | 86   | 85   | 186  | 50   | 97   | 11.6      |

# Blueprint

