



Eye sling hook with latch, grade 80

Product information

Hook is equipped with spring loaded safety latch.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-2

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Part code	WLL ton	For chain Ø mm	K mm	E mm	F mm	R mm	A mm	Weight kg
401300110680	1.12	6	108	24	9	21	20	0.3
401300200680	2	7/8	133	30	11	26	25	0.4
401300320680	3.15	10	167	34	15	39	38	0.9
401300530680	5.3	13	213	39	19	54	43	1.7
401300800680	8	16	255	46	23	64	50	3.2
401301250680	12.5	20	305	40	24	80	62	5.8
401301500680	15	22	348	71	32	80	62	8.5
401302120680	21.2	26	394	81	35	82	64	13
401303150680	31.5	32	480	102	37	112	68	17

Technical data

SPARE PARTS**Spare part set (product code) | Inc. latch, spring and pin/nut****Fits the hook (product code)**

SALKVO6S

SALK6

SALKVO78S

SALK78

SALKVO10S

SALK10

SALKVO13S

SALK13

SALKVO16S

SALK16

SALKVO20S

SALK20

SALKVO22S

SALK22

SALKVO26S

SALK26

SALKVO32S

SALK32

Blueprint

