

Steel Wire Rope POLYASS

Product information



Rope construction: 8 strands with steel wire core.

Marking: According to standard

Standard: EN 12385-4


Note: ISO 4309 Rope Category No: 6-26mm RCN 04

Fill factor: 0.58

Winch rope



Overhead cranes



Tower crane



Part Code	Rope Diameter,	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
101100604270110	6	1,960	Galvanized	sZ	25.1	16.5	Dry	15
101100603270110	6	1,960	Galvanized	zS	25.1	16.5	Dry	15
101100654050111	6.5	1,770	Bright	sZ	26.6	19.3	A-1	17
101100654270110	6.5	1,960	Galvanized	sZ	29.5	19.3	Dry	17
101100653270110	6.5	1,960	Galvanized	zS	29.5	19.3	Dry	17
101100754070111	7.5	1,960	Bright	sZ	39.2	25.7	A-1	23
101100754270110	7.5	1,960	Galvanized	sZ	39.2	25.7	Dry	23
101100753270110	7.5	1,960	Galvanized	zS	39.2	25.7	Dry	23
101101404070111	14	1,960	Bright	sZ	137	89.6	A-1	80
101101404270111	14	1,960	Galvanized	sZ	137	89.6	A-1	80