



Push trolley

Product information

Push trolley for IPE and T beams. The wheels are equipped with duration lubricated ball bearings. The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -10°C - (+)50°C

Finish: Painted, yellow

Standard: EN 13157

Safety factor: 4:1

Part Code	WLL ton	Beam width mm	Minimum radius mm	B mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	Weight kg
502500052200200	0.5	55-220	500	285	3	40	12.5	25	80	198	158	55	5
502500053050200	0.5	55-305	500	385	3	40	12.5	25	80	198	158	55	5.4
502500102200200	1	58-220	700	300	3	31	17	29	96	238	183	68	8.8
502500103050200	1	58-305	700	238	3	31	17	29	96	-	183	68	9.3
502500203050200	2	66-305	900	405	3	31	20	36	110	277	208	80	14.8
502500303050200	3	74-305	1,200	429	-3	31	26	46	132	324	249	100	24.1

Technical data

AXEL OF THE TROLLEY

Product code	Thread	Thread pitch mm
SIVA05H	M24	1,5
SIVA10H	M30	1,5
SIVA20H	M36	1,5
SIVA30H	M42	2
SIVA50H	M48	2

Note! One end is left-hand thread and the other end is right hand thread

Blueprint

