

## Closed Wedge Socket CWS



### Product information

Intended for attaching of wire rope where switching often occur, e.g. blocks of mobilecranes, or to be able to adjust the length of the wire rope. See recommended assembly to get correct results. The wedge socket is delivered complete.

**Marking house and wedge:** Wire  $\varnothing$  mm.

**Material:** Cast alloy steel with high mechanical properties.

**Temperature range:** - 40°C to + 110°C - Use at higher temperatures possible with reduction of WLL.

**Finish:** Blue painted (P) or hot dip galvanized (G).

**Note:** The efficiency of a 6 and 8 strand wire rope/wedge socket connection is 80% of the minimum breaking load of the wire but limited to the minimum breaking load of the socket (MBL).

Part Code	Code	Rope $\varnothing$ range mm	MBL	Finish	Finish	A mm	B mm	C mm	K mm	TA mm	TL mm	Weight kg
121501900175	CWS 303	18-19	40	Painted	P	220	100	34	40	90	254	7
121501900172	CWS 303	18-19	40	Galvanized	G	220	100	34	40	90	254	7
121502200175	CWS 304	20-22	55	Painted	P	225	225	42	47	110	267	9
121502200172	CWS 304	20-22	55	Galvanized	G	225	225	42	47	110	267	9
121502600175	CWS 305	24-26	75	Painted	P	290	130	50	55	125	340	14
121502600172	CWS 305	24-26	75	Galvanized	G	290	130	50	55	125	340	14
121502900175	CWS 306	27-29	90	Painted	P	325	145	60	70	152	385	22
121502900172	CWS 306	27-29	90	Galvanized	G	325	145	60	70	152	385	22

121503200175	CWS 307	30-32	110	Painted	P	360	160	68	75	165	428	30
121503200172	CWS 307	30-32	110	Galvanized	G	360	160	68	75	165	428	30
121503600175	CWS 308	34-36	125	Painted	P	400	180	68	75	165	468	38
121503600172	CWS 308	34-36	125	Galvanized	G	400	180	68	75	165	468	38
121503900175	CWS 309	37-39	150	Painted	P	500	240	72	80	185	572	49
121503900172	CWS 309	37-39	150	Galvanized	G	500	240	72	80	185	572	49
121504200175	CWS 310	40-42	170	Painted	P	600	310	80	90	210	680	65
121504200172	CWS 310	40-42	170	Galvanized	G	600	310	80	90	210	680	65
121504800175	CWS 311	43-48	225	Painted	P	640	325	90	100	225	730	100
121504800172	CWS 311	43-48	225	Galvanized	G	640	325	90	100	225	730	100
121505200175	CWS 312	49-52	280	Painted	P	720	375	100	110	245	820	150
121505200172	CWS 312	49-52	280	Galvanized	G	720	375	100	110	245	820	150
121505800175	CWS 313	54-58	360	Painted	P	775	400	110	120	265	885	175
121505800172	CWS 313	54-58	360	Galvanized	G	775	400	110	120	265	885	175
121506400175	CWS 314	61-64	425	Painted	P	900	470	120	130	290	1,020	230
121506400172	CWS 314	61-64	425	Galvanized	G	900	470	120	130	290	1,020	230
121507600175	CWS 315	72-76	460	Painted	P	1,000	500	130	150	330	1,130	300
121507600172	CWS 315	72-76	460	Galvanized	G	1,000	500	130	150	330	1,130	300
121508600175	CWS 316	81-86	625	Painted	P	1,125	550	135	165	360	1,260	425
121508600172	CWS 316	81-86	625	Galvanized	G	1,125	550	135	165	360	1,260	425

# Blueprint

