

## HFC S Flat Hydraulic Cylinder



### Product information

Holmatro Flat cylinders (HFC) - Spring return

#### Unique specifications:

- Compact, flat version, efficient in case of limited insertion space
- Stroke of 15mm on all models

#### Standard supplied with:

- Standard provided with fixing holes for easy assembly
- Dirt scraper ring
  - Protects against pollution
  - Increases the life span
- Superior seal for an excellent static and dynamic sealing
- Splined plunger, no saddle needed
- High flow female coupler A118

#### Also available:

- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

**Material:** Steel

| Part Code     | Code          | WLL ton | Stroke mm | Closed height mm | Capacity kN/t  | Weight kg |
|---------------|---------------|---------|-----------|------------------|----------------|-----------|
| 5211100112291 | HFC 5 S 1.5   | 5       | 15        | 44               | 50.9 / 5.2     | 1         |
| 5211100112292 | HFC 10 S 1.5  | 10      | 15        | 46               | 99.8 / 10.2    | 1.6       |
| 5211100112293 | HFC 20 S 1.5  | 20      | 15        | 55               | 203.6 / 20.8   | 2.9       |
| 5211100112295 | HFC 30 S 1.5  | 30      | 15        | 60               | 318.1 / 32.4   | 4.2       |
| 5211100112296 | HFC 50 S 1.5  | 50      | 15        | 71               | 510.4 / 52     | 7         |
| 5211100112297 | HFC 75 S 1.5  | 75      | 15        | 80               | 747.9 / 76.3   | 11        |
| 5211100112298 | HFC 100 S 1.5 | 100     | 15        | 90               | 1030.5 / 105.1 | 18.1      |

## Blueprint

