



## Clevis Sling Hook Pewag KHSWP

### Product information

The forged safety catch locks into the tip of the hook, thereby providing excellent protection against lateral shifts. The safety catch mechanism and the clevis load pins are available as spare parts sets and easy and quick to exchange by a competent person.

The forged control markings make it easy to determine discard criteria.

**Material:** Alloy steel

**Marking:** According to standard, CE-marked, Pewag or PW, winner pro or 12, H16, batch code and type.

**Temperature range:** -60°C up to +300°C.

**Finish:** Light blue powdercoated.

**Standard:** EN 1677-2

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 12

| Part Code    | Code     | WLL<br>ton | LC<br>kN | a<br>mm | b<br>mm | d<br>mm | e<br>mm | g1<br>mm | h<br>mm | Weight<br>kg |
|--------------|----------|------------|----------|---------|---------|---------|---------|----------|---------|--------------|
| 403300240030 | KHSWP 7  | 2.36       | 47       | 19      | 101     | 9       | 105     | 36       | 26      | 0.85         |
| 403300300030 | KHSWP 8  | 3          | 60       | 19      | 101     | 10      | 105     | 36       | 26      | 0.85         |
| 403300500030 | KHSWP 10 | 5          | 100      | 26      | 118     | 14      | 121     | 41       | 33      | 1.68         |
| 403300800030 | KHSWP 13 | 8          | 160      | 30      | 147     | 17      | 148     | 49       | 43      | 2.99         |
| 403301250030 | KHSWP 16 | 12.5       | -        | 35      | 176     | 21      | 173     | 59       | 51      | 5.1          |

Blueprint

